

CHARACTERISTIC DATE

CHARACTERISTIC DATA

Code	Name	Normal Operating Conditions										Average Characteristics—Class A Operation										Tube Symbol Dimensions Connec- tion Fig.	Remarks
		Cathode Htr. or Fil. Type	Volts	Class of Operation	Plate Potential Volts	Plate Current Amperes	Control- Grid Bias Volts	Screen- Grid Bias Volts	Max. R.F. Current Amperes	Power Output Watts	Max. Plate Dissipa- tion Watts	Plate Potential Volts	Plate Current Amperes	Amplifi- cation Factor	Plate Resistance Ohms	Trans- former Micro- amperes	Maximum Dimensions Inches Height Dia.	Socket					
101D	Triode	O-F	4.5	1.0	A Audio	130	0.0075	-9		0.065		130	0.0077	6.2	5800	1070	4 1/2	1 1/8	100L	100R	1		
101F	"	O-F	4.15	0.50	A "	130	0.0068	-8		0.090		130	0.0068	6.5	5800	1120	4 1/2	1 1/8	100L	100R	1		
101FA	"	O-F	4.15	0.50	A "	130	0.0044	-8		0.094		130	0.0044	8.9	6100	1460	4 1/2	1 1/8	100L	100R	1		
102D	"	O-F	2.1	1.0	A "	130	0.0008	-1.5		20 Peak Volts		130	0.0008	29.6	58000	510	4 1/2	1 1/8	100L	100R	1		
102F	"	O-F	2.1	0.50	A "	130	0.00085	-1.5		22 Peak Volts		130	0.00085	31	50000	620	4 1/2	1 1/8	100L	100R	1		
104D	"	O-F	4.5	1.0	A "	130	0.025	-20		0.160		130	0.025	2.5	2100	1180	4 1/2	1 1/8	100L	100R	1		
205D	"	O-F	4.5	1.6	A "	350	0.029	-22.5		0.875		350	0.029	7.3	3800	1940	4 1/2	2 3/8	100N	100R	7		
205E	"	O-F	4.5	1.6	A "	350	0.029	-22.5		0.875		350	0.029	7.3	3800	1940	4 1/2	2 3/8	100N	100R	7		
212E	"	T-F	14.0	6.0	B R-F Ampl.	2000	0.200	-120	5	150	275	2000	0.165	16	1900	8500	13 3/4	3 3/4	147A	115B	4		
215A	"	O-F	1.0	0.25	A Audio	60	0.002	-3		0.0029		60	0.002	5.7	13500	430	2 1/8	1 1/8	125B	115B	1		
220C	"	W-F	21.5	41.0	B R-F Ampl.	11000	0.75	-250	20	2750	10000	10000	0.64	40	8000	5000	20 7/8	6 3/8	132A	132A	50		
228A	"	W-F	21.5	41.0	B "	5000	0.65	-325	20	1100	5000	5000	0.9	16	2500	6500	18	3 1/2	126A	133A	48		
231D	"	O-F	3.1	0.060	A Audio	30	0.0021	-3		0.0045		30	0.0021	8.4	16300	510	4	1 3/8	132A	132A	24		
232B	"	W-F	20.0	60.0	B R-F Ampl.	17500	1.5	-500	40	9000	25000	15000	1.35	40	6150	6500	21 1/8	6	133A	133A	50		
236A	"	W-F	21.5	41.0	B "	15000	1.0	-375	25	5000	20000	15000	1.0	40	6300	6450	30	3 3/4	133A	133A	50		
240B	"	W-F	21.5	41.0	B "	12000	1.0	-250	60	4000	10000	10000	0.64	40	8000	5000	25 1/8	6 3/8	Spl. Mtg	Spl. Mtg	50		
241B	"	T-F	14.0	6.0	B "	2000	0.200	-120	5	150	275	2000	0.165	16	1900	8500	14 1/2	3 3/8	145A	145A	3		
242C	"	T-F	10.0	3.25	B "	1250	0.120	-90	5	50	100	1250	0.088	12.5	3500	3800	7 1/8	2 1/8	144A	144A	26		
244A	"	H	2.0	1.6	A Audio	135	0.0055	-6		0.049		135	0.0055	10.1	10000	1010	4 3/8	1 1/8	141A	141A	27		
245A	"	H	2.0	1.6	A R-F Ampl.	135	0.0048	-1.5		0.037		135	0.0048	135	180000	750	5 1/4	1 1/8	141A	141A	27		
246A	"	O-F	3.3	0.100	A Audio	135	0.0032	-4.5		0.037		135	0.0032	285	725000	390	5 1/4	1 1/8	143B	143B	10		
247A	"	H	2.0	1.6	A Audio	135	0.0062	-4.5		0.037		135	0.0062	15.2	16000	940	4 3/8	1 1/8	141A	141A	26A		
251A	"	T-F	10.0	1.60	B R-F Ampl.	3000	0.100	-300	15	400	1000	2500	0.240	10.5	2750	3800	21 1/8	6	142A	142A	50		
252A	"	O-F	5.0	2.0	A Audio	450	0.060	-60		7.0		450	0.060	5.1	1900	3450	6 3/4	2 1/8	143B	143B	2		
254A	"	T-F	5.0	3.25	B R-F Ampl.	750	0.040	-40		10	20	750	0.027	80	80000	1000	6 1/8	2 1/8	143B	143B	12		
254B	"	T-F	7.5	3.25	B R-F Ampl.	750	0.050	-70		12.5	25	750	0.033	100	86000	1160	6 1/8	2 1/8	143B	143B	12		
257A	"	O-F	3.1	0.060	A Audio	90	0.0021	-3		0.0045		90	0.0021	8.4	16300	510	4 3/8	1 1/8	143B	143B	13		
259A	"	H	2.0	1.6	A R-F Ampl.	180	0.0055	-1.5		75		180	0.0055	5.50	400000	1380	5 1/4	1 1/8	141A	141A	27		
259B	"	H	2.0	1.6	A R-F Ampl.	180	0.0055	-1.5		75		180	0.0055	5.50	400000	1380	5 1/4	1 1/8	141A	141A	27		
261A	"	T-F	10.0	3.25	B R-F Ampl.	1250	0.125	-100		50	100	1250	0.088	12	3000	4000	7 1/8	2 1/8	145A	145A	3		
262B	"	H	10.0	0.32	A Audio	135	0.0028	-4.5		0.035		135	0.0028	15.7	17500	900	4 3/4	1 1/8	143B	143B	14		
264C	"	O-F	1.5	0.300	A Audio	100	0.0021	-8		0.033		100	0.0021	7.2	12400	880	4	1 3/8	143B	143B	24		
268A	"	T-F	5.0	3.25	B R-F Ampl.	750	0.050	-165	3	12.5	25	750	0.025	5	6250	800	6 1/8	2 1/8	143B	143B	17		
270A	"	T-F	10.0	9.75	B "	3000	0.175	-180	10	175	350	2500	0.120	16	2800	5700	17	4	Spl. Mtg	Spl. Mtg	48		
271A	"	H	5.0	2.0	A Audio	400	0.0375	-30		2.8		400	0.0375	8.3	2830	2920	6 3/4	2 1/8	141A	141A	26		
272A	"	H	10.0	0.32	A "	140	0.0054	-15		0.12		140	0.0054	5.6	7400	760	4 3/8	1 1/8	141A	141A	26		
273A	"	O-F	1.2	1.6	A "	200	0.047	-45		1.9	17	200	0.047	2.8	1030	2770	5 5/8	2 1/8	143B	143B	2		
276A	"	T-F	10.0	3.0	B R-F Ampl.	1250	0.125	-100		50	100	1250	0.088	12	3000	4000	7 1/8	2 1/8	145A	145A	3		
278A	"	T-F	10.0	15.6	B "	3000	0.400	-110		410	800	3000	0.200	400	105000	3800	21 1/8	6	142A	142A	54		
279A	"	T-F	10.0	21.0	B "	3000	0.600	-325		600	1200	2500	0.300	10	2000	5000	21 1/8	6	142A	142A	54		
281A	"	O-F	5.0	1.6	A Audio	130	0.035	-90		2.2		130	0.035	5	3400	1470	6 3/4	2 1/8	141A	141A	25		
282A	"	T-F	10.0	3.0	B R-F Ampl.	1000	0.100	-90		33	70	1000	0.070	100	70000	1430	6 1/8	2 1/8	143B	143B	12		
282B	"	T-F	10.0	3.0	B "	1000	0.100	-90		33	70	1000	0.070	100	70000	1430	6 1/8	2 1/8	143B	143B	12		
283A	"	H	2.0	1.6	A R-F Ampl.	180	0.0059	-1.5		40	85	180	0.0059	5.85	430000	1360	5 1/4	1 1/8	141A	141A	27		
284D	"	T-F	10.0	3.25	A Audio	1250	0.064	-220		0.65		1250	0.064	4.8	1900	2500	7 1/8	2 1/8	145A	145A	3		
285A	"	H	2.0	1.6	A R-F Ampl.	180	0.0088	-12		150		180	0.0088	135	153000	880	5 1/4	1 1/8	141A	141A	28		
X 286A	"	H	2.0	1.6	A R-F Ampl.	180	0.0092	-1.5		75		180	0.0092	8.50	700000	1200	5 1/4	1 1/8	144B	144B	37		
X 290A	"	H	10.0	0.32	A "	180	0.0045	-1.5		75		180	0.0045	1160	950000	1220	5 1/4	1 1/8	144B	144B	37		
X 291A	"	H	10.0	0.32	A "	180	0.0045	-1.5		75		180	0.0045	275	100000	650	5 1/4	1 1/8	M.C.L.	M.C.L.	31		
	Pentagrid Converter	H	100	0.32	Osc. Mod.	(180) (Osc.)	0.0045	-7.5 (Osc. Grid)													Screen Grid Current—0086 Amp.		

KEY TO DESIGNATIONS

A—Average
C—Converter
E—Element
F—Filament Type Cathode
G—Gas Filled
H—Heater Type Cathode
M—Mercury
Mod—Modulator
O—Osc. Coiled
Osc—Oscillator
P—Plate Modulated
Full Wave
Rh—Half Wave
Sect—Section
SGM—Suppressor Grid Modulated
T—Thermostatic Tungsten
V—High Vacuum
X—Rated "A&M Only"

Screen Grid Current—0.008 Amp.

See Remarks Column.

CHARACTERISTIC DATE

CHARACTERISTIC DATA

Code No.	Name	Cathode Htr. or Fil.		Class of Operation	Normal Operating Conditions						Average Characteristics—Class A Operation						Maximum Dimensions		Tube Symbol and Base Connections	Remarks	Code No.	
		Type	Volts		Plate Power, Watts	Control Grid Bias, Volts	Screen Grid Potential, Volts	Max. R-F Current, Amperes	Power Output, Watts	Max. Plate Dissip. Watts	Plate Power, Watts	Plate Current, Amperes	Ampl. Factor	Plate Resistance, Ohms	Trans-conductance, Micro-mhos	Height	Dia.	Socket				Fig.
X 292A	Duodiode (Triode)	H	10.0	A Audio (Triode Sect.)	135	0.0021	-6			0.041		135	0.0021	13.3	20000	665	5 1/4	1 1/4	144B	31	Each Diode, E _b =9V, I _b =0.0022 Amp.	292A
X 293A	Pentode	H	10.0	A Audio	180	0.0145	-18			1.2		180	0.0145	105	100000	1050	4 1/4	1 1/4	144B	33		293A
X 294A	Pentode	H	10.0	A " "	180	0.0145	-18			1.2		180	0.0145	105	100000	1050	5 1/4	1 1/4	141A	28A		294A
295A	Tetrode	T-F	10.0	B R-F Ampl.	1250	0.105	-45			42.5		1250	0.080	25	6000	4200	7 1/8	2 1/8	145A	3		295A
296A	"	W-F	27.0	B " "	18000	4.2	-500			25000		18000	4.2	32	1450	22000	51 1/8	9 1/8	146A	50	Water Cooled	296A
300B	"	O-F	5.0	A " "	300	0.060	-61			6		300	0.060	3.8	700	5400	6 1/2	2 1/8	143B	58	For either Bayonet or Push Type Socket	300B
X 303A	Duodiode (Triode)	H	2.0	A " (Triode Sect.)	135	0.002	-6			0.040		135	0.002	13.5	21000	640	5 1/4	1 1/4	144B	31	Each Diode, E _b =9V I _b =0.0021 Amp.	303A
304B	Tetrode	T-F	3.25	B R-F Ampl.	1250	0.080	-110			25		1250	0.040	11	2000	5500	6 1/8	2 1/8	143B	19		304B
305A	Tetrode	T-F	10.0	B " "	1000	0.090	-135			30		1000	0.090	56	40000	1400	7 1/8	2 1/8	143B	20	Max. Screen Dissipation 6 Watts	305A
306A	Pentode	O-F	2.75	C R-F Ampl. (PM)	300	0.036	-50 (Approx.)			7		250	0.043	250	62000	4050	6 1/4	2 1/8	141A	30	Max. Screen Dissipation 6 Watts	306A
307A	"	O-F	5.5	C R-F Ampl. (SGM)	500	0.040	-35 (Approx.)			6		250	0.050	120	30000	4000	6 1/4	2 1/8	141A	35	Max. Screen Dissipation 6 Watts	307A
308B	Tetrode	T-F	14.0	B R-F Ampl.	1750	0.215	-220			125		1500	0.167	8	1070	7500	13 1/8	3 3/4	147A	4		308B
309A	Pentode	H	10.0	A Audio or R-F Ampl.	180	0.0048	-1.5			0.25		180	0.0048	1100	1000000	1100	4 1/2	1 1/4	141A	28A	Variable Mu	309A
310A	"	H	10.0	A " " " "	135	0.0055	-3			0.25		135	0.0055	1200	650000	1800	4 1/2	1 1/4	144B	37		310A
310B	"	H	10.0	A " " " "	135	0.0055	-3			0.25		135	0.0055	1200	650000	1800	4 1/2	1 1/4	144B	37	Low Hum	310B
311A	"	H	10.0	A " " " "	135	0.030	-15			2		135	0.030	122	43000	2800	4 1/2	1 1/4	141A	28A		311A
312A	"	T-F	10.0	C R-F Ampl. (SGM)	1250	0.050	-50 (Approx.)			23		1000	0.050	1100	290000	3800	7 1/4	2 1/8	144B	38		312A
316A	Tetrode	T-F	2.0	R-F (PM)	400	0.080	Adjust (-17)			6.5		450	0.067	6.5	2700	2400	2 1/2	2 1/8	Spl. Mfg.	52		316A
320A	"	W-F	35.0	B R-F Ampl.	1800	12.5	-300			75000		15000	8.0	30	965	31100	94	10 1/4	Spl. Mfg.	51	Water Cooled	320A
322A	Pentode	T-F	10.0	C R-F Ampl. (SGM)	2000	0.080	-85 (Approx.)			53		125	0.0625	1400	350000	4000	9 1/8	2 1/8		53		322A
328A	"	H	7.5	A Audio or R-F Ampl.	135	0.0055	-3			0.25		135	0.0055	1350	750000	1800	4 1/2	1 1/4	144B	37		328A
329A	"	H	7.5	A " " " "	135	0.030	-15			2		135	0.030	122	43000	2800	4 1/2	1 1/4	141A	28A		329A
331A	Tetrode	T-F	10.0	B " 2 Tubes	1500	0.040	-20			370		125	0.030	40	8900	4500	8 1/2	2 1/8	145A	55		331A
332A	Pentode	T-F	10.0	B R-F Ampl.	2000	0.064	-40			53		125	0.0625	1400	350000	4000	9 1/8	2 1/8		39		332A
336A	"	H	10.0	A Audio	250	0.030	-14			3.5		250	0.030	336	80000	4200	4 1/8	1 1/4	144B	33	Variable Mu	336A
337A	"	H	10.0	A Audio or R-F Ampl.	135	0.0063	-3			3		135	0.006	1070	650000	1650	4 1/2	1 1/4	144B	37	Max. Screen Dissipation 12 Watts	337A
339A	"	O-F	5.0	B " " "	400	0.120	-90			30		400	0.073	96	20000	4800	7 1/8	2 1/8	141A	35A		339A
340A	Tetrode	W-F	20.0	B R-F Ampl.	18000	1.1	-450			9000		15000	1.3	40	5860	6520	21 1/8	6 1/2	132A	50	Water Cooled	340A
342A	"	W-F	20.0	B " "	18000	1.4	-450			8500		15000	1.3	40	5860	6520	21 1/8	6 1/2	132A	50	Water Cooled	342A
343A	"	W-F	21.5	B " "	15000	0.70	-350			3500		10000	0.64	40	5920	6750	20 7/8	6 1/2	133A	50	Water Cooled	343A
343A	"	W-F	21.5	B " "	15000	0.66	-300			20		5000	0.0058	40	5920	6750	21 1/8	7 1/2	154A	42	Air Cooled	343A
347A	"	H	6.3	A Audio	135	0.0028	-4.5			0.035		135	0.0025	15.7	17500	900	1 1/4	1 1/4	132A	50		347A
348A	Pentode	H	6.3	A Audio or R-F Ampl.	135	0.0055	-13			0.25		135	0.005	1200	650000	1800	4 1/2	1 1/4	132A	43		348A
349A	"	H	6.3	A Audio Ampl.	250	0.030	-14			3.5		250	0.030	336	80000	4200	4 1/2	1 1/4	132A	44	Low Hum	349A
350A	Tetrode	H	6.3	B A Audio or R-F Ampl.	400	0.085	-20			24		400	0.055	430	67000	6400	5 1/2	1 1/4	141A	41	Max. Screen Dissipation 4 Watts	350A
350B	"	H	6.3	B A Audio Ampl.	400	0.085	-20			20		400	0.055	430	64000	6200	5 1/2	1 1/4	141A	36	Max. Screen Dissipation 4 Watts	350B
352A	Duodiode (Triode)	H	10.0	A Audio (Triode Sect.)	135	0.0021	-6			0.042		135	0.0021	13.3	20500	650	4 1/4	1 1/4	144B	31	Each Diode, E _b =9V I _b =0.0051 Amp.	352A
356A	Tetrode	T-F	5.0	C R-F Ampl. (PM)	1250	0.100	-100			85		50	0.100	50	13000	3800	5	2 1/8	152A	24		356A
357A	Tetrode	T-F	10.0	C " "	3000	0.240	-270			550		350	0.500	30	3500	9000	5 1/8	5 1/8	153A	62		357A
361A	Pentode	F	0.020	A Audio	45	0.0004				0.006		36	0.0004	160	64000	250	1 1/8	%	None	48	Audio	361A
362A	"	F	1.4	A Audio	45	0.00126				0.006		45	0.00125	160	280000	570	1 1/8	%	None	62	Audio	362A
363A	"	T-F	10.0	C R-F Amp.*	3000	0.450	-250			1000		350	0.500	300	25000	12000	3 1/8	5 1/8	Spl. Mfg.	60	Unmodulated—For Frequency Mod. Use	363A
364A	Tetrode	T-F	5.0	C R-F Ampl. (PM)	1250	0.100	-100			85		50	0.100	50	11000	4500	3 3/8	2 1/8	A5A	61		364A
366A	Pentode	H	6.3	A R-F Ampl.	200	0.016	-2			20		200	0.016	2700	10000	10000	1 1/8	2 1/8	Octal	63	Not in production	366A
367A	Tetrode	H	6.3	B A R-F	400	0.085	-20			20		400	0.053	400	64000	6200	4 1/8	2 1/8	Octal	63		367A
368A	Tetrode	T-F	1.0	Dec.	300	0.075	-300			3*		30	0.060	23	4500	2000	2 1/2	2 1/8		64	Below 1000 MC.	368A
370A	"	F	10.0	C*	3500	1.40	-300			3000		1750	3000	0.500	2500	10000	16	6 1/4	153A	45	Frequency Modulated	370A

CHARACTERISTIC DATA

RECTIFIERS

Code No.	Classification	Cooling	Cathode		Maximum Dimensions		Max. Peak Inverse Anode Voltage	Max. Average Anode Current	Maximum Instantaneous Anode Current		Maximum Average Anode Current		Maximum Time of Anode Averaging, Seconds	Maximum Ambient Temperature Range, Deg. C.	Socket	Tube Symbol and Base Connections Figure	Code No.
			Type	Volts a-c	Ampere	Height			Diameter	In Phase Operation	Quadrature Operation	In Phase Operation					
214E	Rh-V	Air	W-F	10.0	3.25	7 1/8	2 1/8	3,500	0.000	2.5	—	0.04	—	5	145A 132A 133A 132A	6	214E
222A	Rh-V	Water	W-F	21.5	41	18	3 1/8	25,000	5	—	—	—	—	—	132A 133A 133A	8	222A
233B	Rh-V	"	W-F	21.5	41	20 3/4	4 1/8	50,000	5	—	—	—	—	—	132A 133A 133A	8	233B
237A	Rh-V	"	W-F	20.0	61	23 1/4	4 1/8	50,000	8	2.5	—	—	—	5	132A 133A 143B 138B 138A	8	237A
249B	Rh-Hg	Air	O-F	2.5	7.5	7 3/4	2 1/8	7,500	—	1.0	—	0.25	—	5	138A 138B 139A	15	249B
253A	Rh-Hg	"	O-F	2.5	3.0	6 1/8	2 3/8	3,500	—	—	—	—	—	—	138A	8	253A
255B	Rh-Hg	"	O-F	5.0	19	19 1/8	5 1/8	20,000	—	8	16	2	4	30	Spl. Mfg. 138B 139A	8	255B
258B	Rh-Hg	"	O-F	2.5	7.5	7 1/8	2 1/8	7,500	—	2.5	—	0.04	—	5	139A	8	258B
263A	Rh-Ar	"	O-F	2.5	15	10 3/4	3 1/4	100	—	12.5	—	3.2	—	15	280A Plug & 139A 139A	9	263A
263B	Rh-Hg	"	O-F	2.5	15	10 3/4	3 1/4	100	—	20	—	5	—	15	280A Plug & 139A 139A	9	263B
266B	Rh-Hg	"	O-F	5.0	42	21 3/4	7	20,000	—	20	40	5	10	60	Spl. Mfg. 138B 138A	57	266B
267B	Rh-Hg	"	O-F	5.0	6.75	8 1/8	2 3/8	7,500	—	4	8	1	2	15	{ 15-30 30-40 (30-40 Forced Air) 10-50	8	267B
274A	Rh-V	"	O-F	5.0	2.0	5 5/8	2 3/8	1,500	0.8	—	—	—	—	—	143B Ocel Mogul	11	274A
274B	Rh-V	"	O-F	5.0	2.0	5 5/8	2 3/8	1,500	0.8	24	—	6.0	—	—	143B Ocel Mogul	32	274B
288A	Rh-Ar	"	W-F	2.2	18	6 1/8	3 1/8	300	—	24	—	—	—	—	143B Ocel Mogul	56	288A
289A	Rh-Ar	"	W-F	2.2	18	6 1/8	3 1/8	375	—	24	—	6.0	—	—	143B Ocel Mogul	56	289A
301A	Rh-Hg	"	O-F	5.0	3.0	6 1/2	2 3/8	1,800	—	2 per Anode	—	0.5 per Anode	—	5	143B Ocel Mogul	11	301A
314A	Rh-Hg	"	O-F	5.0	5.0	6 1/2	2 3/8	300	—	5 per Anode	—	1.25 per Anode	—	5	143B Ocel Mogul	11A	314A
315A	Rh-Hg	"	O-F	5.0	10.0	12 1/4	3 3/8	12,500	—	4	8	1	2	15	138B 139A	8	315A
319A	Rh-Hg	"	O-F	5.0	6.75	8 1/2	2 3/8	7,500	—	4	8	1	2	15	148A	21	319A
321A	Rh-Hg	"	O-F	5.0	10.0	11 7/8	3 3/8	12,500	—	4	8	1	2	15	148A	21	321A
324A	Rh-V	"	W-F	5.0	3.0	5 5/8	1 3/8	12,000	0.020	4	8	1	2	15	143B	18	324A
327A	Rh-Ar	"	W-F	2.0	12	4 7/8	2 1/4	275	—	8	—	2	—	—	Gen. Elec. 275768	56	327A
345A	Rh-V	"	H	6.3	1.0	4 1/4	1 3/8	1,000	0.500	R-M-S Alternating Voltage per Anode— Choke Input Filter 400 Volts Condenser Input Filter 350 Volts				—	141A	40	345A
351A	Rh-V	"	H	6.3	1.0	4 1/4	1 3/8	1,000	0.500					—	Ocel	47	351A

KEY TO DESIGNATIONS

A—Argon Gas E1—Element (C)—Gas Filled Hg—Mercury O—Oxide Coated PM—Phase Modulated Rh—Half Wave SGM—Suppressor Grid Modulated V—High Vacuum
 Con.—Converter F—Filament Type Cathode H—Heater Type Cathode Mod.—Modulator Osc.—Oscillator R—Full Wave Sect.—Section T—Theorized Tungsten W—Tungsten X—Rare "A&M Only"

CHARACTERISTIC DATE

THYRATRONS

Code No.	Gas	Cathode		Maximum Dimensions, Inches		Max. Time of Averaging, Seconds	Max. Peak Voltage Between Anode and Grid, Volts	Operating Ambient Temperature Range, Degrees C.		Operating Condensed Ambient Temperature Range, Degrees C.		Nominal Deflection Time, Microseconds	Socket	Tube Symbol & Base Connections Figure	Code No.
		Type	Volts	Amps.	Height	Diameter									
256A	Ar	H	2.3	1.7	4 1/8	1 1/8	0.075	—	—	—	—	1000	141A	26A	256A
269A	Ar	O.F.	2.2	0.55	4 1/8	2 3/8	0.120	—	—	—	—	100	143B	24A	269A
277A	Ar	H	5.0	2.8	6 3/4	2 1/8	0.300	—	—	—	—	100	141A	26A	277A
287A	Hg	O.F.	2.5	7.0	6 3/8	2 3/8	0.64	—	—	—	—	1000	141A	29	287A
297A	Ar	O.F.	1.75	0.350	4	1 3/8	0.100	—	—	—	—	1000	143B	24A	297A
323A	Ar-Hg	O.F.	2.5	7.0	6 3/8	2 3/8	0.100	—	—	—	—	1000	141A	29	323A
338A	Ar	H	10.0	0.5	4 1/8	1 3/8	0.600	—	—	—	—	1000	141A	26A	338A
354A	Hg	O.F.	2.5	16.0	9 1/2	3 3/8	16.0	—	—	—	—	1000	141A	16	354A
355A	Ar-Hg	O.F.	2.5	16.0	9 1/2	3 3/8	16.0	—	—	—	—	1000	141A	16	355A

COLD CATHODE TUBES

Code No.	Classification	Maximum Dimensions, Inches		Nominal Control-Cap Breakdown Voltage, D.C.	Nominal Control-Cap Sustaining Voltage, D.C.	Minimum Breakdown Voltage, D.C.	Nominal Main-Cap Sustaining Voltage, D.C.	Maximum Current at 130 Volts, Microamperes	Direct Forward Current Rating For Life, Milliamperes			Peak Reverse Current, Electrons	Nominal Deionization Time, Milliseconds		Socket	Tube Symbol & Base Connections Fig.	Code No.
		Height	Diameter						100 Hrs.	1000 Hrs.	5000 Hrs.		Main	Control			
313C	3 E.I.-G	3 1/2	1 3/8	70	60	150	75	5	35	20	15	5	10	3	143B	22	313C
313CA	3 E.I.-G	3 1/2	1 3/8	72	60	200	75	5	18	10	8	5	10	3	143B	22	313CA
313CB	3 E.I.-G	3 1/2	1 3/8	70	60	185	75	5	18	10	8	5	10	3	143B	22	313CB
333A	3 E.I.-G	3 3/4	1 3/8	70	60	150	75	5	35	20	15	5	10	3	Bkt. Mtg.	23A	333A
346A	3 E.I.-G	3 1/2	1 3/8	70	60	225	80	5	35	20	15	5	10	3	"	23	346A
353A	3 E.I.-G	3 3/4	1 3/8	70	60	150	75	5	35	20	15	5	10	3	"	23	353A
358A	2 E.I.-G	1 1/2	3/4	70	60	180	80	100	18	10	7.5	1	10	3	Clip Mtg.	49	358A
359A	3 E.I.-G	2 1/2	3/4	75	65	180	80	100	18	10	8	1	10	3	"	59	359A

CATHODE RAY TUBES

Code No.	Application	Cathode		Maximum Length, Inches	Maximum Screen Diameter, Inches	Fluorescent Characteristic	Potential on Focusing Electrode E _f , Max.	Potential on Accelerating Electrode E _a , Max.	Ratio E _a to E _f to Produce Focus	Potential on Modulating Electrode E _m	Ratio E _m to E _f to Enlarge Spot	Potential of One Pair of Plates for Deflection of Spot	Socket	Tube Symbol and Base Connections Fig.	Code No.
		Type	Volts	Amps.											
325A-B-C	Note 1	H	5.0	0.55	16 1/2	4 1/2	1500	5000	0.2-0.3	Variable	0.012-0.020	E _f /15	141A	46	325A-B-C
326A-B-C	Note 1	H	5.0	0.55	22	7 1/2	1500	5000	0.2-0.3	Variable	0.012-0.020	E _f /25	141A	46	326A-B-C
330A-B-C	Note 1	H	5.0	1.65	23 1/2	7 1/2	1500	5000	0.2-0.3	Variable	0.012-0.025	E _f /25	141A	45	330A-B-C

Note 1. Application and Fluorescent Characteristics for Types A, B and C (CODE NO.)

325A, 326A, 330A

Visual Observation and Photography with Green-Sensitive Film

325B, 326B, 330B

Observation and Photography of Non-recurrent and Low Frequency Phenomena

325C, 326C, 330C

Photography with Blue-Sensitive Film

Blue, Medium Resistance

Blue-Green, Long Persistence

Blue, Highly Active

Blue, Highly Active

Blue, Highly Active

Blue, Highly Active

KEY TO DESIGNATIONS

A—Alcon Gas E—Element G—Gas Filled H—Heater Type Cathode Mod—Modulator O—Oscillator PM—Paced Modulated R—Full Wave SGM—Suppressor Grid Modulated V—High Vacuum X—Rare "AAM Only"

Con—Converter F—Filament Type Cathode

H—Heater Type Cathode

Mod—Modulator

O—Oscillator

PM—Paced Modulated

R—Full Wave

SGM—Suppressor Grid Modulated

V—High Vacuum

X—Rare "AAM Only"

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

October 14, 1946
Page 9 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
101-D	S	Low power filamentary triode used in carrier and voice frequency equipment. (Merchandise control.)		
101-F	S	Low power filamentary triode used in carrier and voice frequency equipment. (Merchandise control.)		
101-FA	S	Similar to 101-F, except for modifications designed to obtain higher gain. (Merchandise control.)		
101-H	M.D.	Three element filament type tube. Used in submarine cable terminal equipment. Similar in characteristics to 101-D tube.		
101-L	S	Low power filamentary triode used in voice and carrier frequency equipment. (Merchandise control.)		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

Western Electric Company
Radio Division
Department 9715

October 14, 1946
Page 10 of 86 pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

CHARACTERISTIC DATA

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
101-M	S	Low power filamentary triode used in voice frequency equipment where quick heating of the filament is required. (Merchandise control.)		
102-D	S	Filamentary voltage amplifier triode used in voice and carrier frequency equipment. (Merchandise control.)	Sylvania	102-D
102-F	S	Filamentary voltage amplifier triode used in voice and carrier frequency equipment. (Merchandise control.)		
102-H	M.D.	Three element filament type tube. Used in submarine cable terminal equipment.		
102-L	S	Filamentary voltage amplifier triode used in voice and carrier frequency equipment. (Merchandise control.)		
(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value. (*) With modifications.				

Western Electric Company
Radio Division
Department 9715

Oct. 14, 1946
Page 11 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

CHARACTERISTIC DATE

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
104-D	S	Filamentary power amplifier triode used in voice and carrier frequency equipments requiring greater power outputs than can be obtained from 101-D or 101-F.		
CK-108		Manufactured by Raytheon. We use it in 100 type loudspeakers. Kearny Telephone Merchandise maintains stock.	Raytheon	
111-A		Ballast lamp - see the general bulletin.		
112-A		Ballast lamp.		
113-A		Ballast lamp.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 14 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
203-A	-	Code number in our series but not our tube at present. Our 203-A (M.D. years ago) was the VT-1.	Amperex United Elec.	
204-A	-	Code number in our series but not our tube.	Field	
205-F	S	Moderate power filamentary triode. Replaces previous 205 types. Used as an amplifier, oscillator or modulator; 13-C, 25-B, 25-D, 32-A, 34-A, 34-B, 35-A, 40-A, 42-A, 45-A, 46-C, 46-D, 8-C, 9-A, 11-A, 17-B, 18-B, 25-C, 51-A, 60-A, 70-A, 79-A, D-92080 and D-85808 Amplifiers; 1-B, 3-A, 3-B, 4-A, 6-B, 8-A, 8-B, 9-A, 9-B, 9-C, 11-A, and 13-A Transmitters; 308-A R.T.E., 9-A Oscillators; 6035-A and B, 6040-A, 6041-A Audiphones; 208-C and 209-A Radio Tel. Equipments; 700-A, 700-B, 701-A, 706-A and 708-A Control Cabinets; D-90873 Oscillator; D-90684 Oscillator Amplifier, 50 K.W. Equipments, 9-A Speech Input Equipments. Also used by E.R.P. and Telephone Co.	Sylvania Amperex R. C. A.	1602
208-A	M.D.	Triode, replaced by 205-F.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 16 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - for Distribution Only Within the Company

CHARACTERISTIC DATE

Code Number	Price Category	Description & Material in Which Used	Competition	Code
212-E	M	Transmitting filamentary triode. Replaces 212-D, 5-C, 6-B, 7-A and 306-A Transmitters. Also used 12-B Radio Transmitters (301-B, 302-B, 303-B and 304-B Equipments) in place of 270-A. (D-98653 Oscillator Modulator unit - modified 12-B Transmitter.) 50 K.W. Trans. (1) D-156000 Radio Transmitter Transoceanic, also used by long lines. We had JAN type approval and so did Federal.	Federal Amperex Rogers-Electronic (Toronto) R.C.A. Westinghouse United Elec.	212-E 212-E AR-300 849* WL-849* 312-E
214-E	M.D.	Half wave high vacuum rectifier. D-86771, D-86823, D-87910, D-88823 Panels. Train Dispatching Equipment. 60-B Vacuum Tube Rectifier. Use 242-C after strapping terminals P and G of the 60-B Rectifier; then 214-E or 242-C can be used interchangeably.	R.C.A.	217-A
215-A	S	Small filamentary triode. A. T. & T. uses in 23-A Amplifier. Old Navy number was 38015.		
216-A	M.D.	Amplifier or oscillator. Train Dispatching Equipment. 7-A Amplifier. Old 12-A Loudspeaking outfit (still some in use on Mexican Government Railway System). Recommend 101-D even though it will not have the long life; it is cheaper in the long run.		

{S} Small tube. {M} Medium value. {M.D.} Manufacture discontinued. {L} Large value.
{*} With modifications.

Western Electric Company
Radio Division
Department 9715

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

September 10, 1946
Page 17 of 86 Pages

CHARACTERISTIC DATE

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
217-A	M.D.	Rectifier to supply plate potential for amplifiers. The JAN-217-A is not our tube (RCA and Lewis Electronics) but it is identical with our old 214-E (replaced by 242-C).		
217-C	-	Half-wave high vacuum rectifier, described in Spec. JAN-217-C not our tube (Amperex, G.E., RCA, Lewis Electronics & Westinghouse).		
219-A&D	M.D.	Rectifier.		
220-B	M.D.	Filamentary water cooled triode tube used in 5-C Radio Transmitter. Water cooled Broadcasting Tube 10 KW. D-96847 R.T.E. (Replacing 5-C.) Circuits have been changed to use either 220-C or 343-A.	Federal	320-B
220-C	L	Filamentary water cooled triode 10 KW. Replaces 220-B. Used in old 5 KW types R.T.E. up to (and optional in) 405-A-1 and 2 R.T.E.	Amperex Federal R.C.A.	F-320-B 892*
220-GA	L	Air cooled 220-C, 405-B-1 and 405-B-2 R.T.E. (optional along with 343-AA).	Amperex?	

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

Western Electric Company,
Radio Division,
Department 9715

October 14, 1946
Page 18 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

CHARACTERISTIC DATE

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
221-D	M.D.	Triode.		
222-A	L	Half wave, water cooled Rectifier, 25 KV, 5-C Radio Transmitter using same water jacket as 233-A and 237-A tubes.	Federal Amperex	322-A 222-A*
222-B	M.D.	Replaced by 222-A. Half wave, high voltage, water cooled rectifier tube. 5 KW R.T.E. Rated manufacture discontinued in 1944. Had round terminals rather than blade type which means that the connectors must be changed before using the 222-A. If 233-B is in manufacture, it can be used interchangeably.	Federal Amperex	F-322-A 222-A
223 -A	M.D.	Triode.		
224-A, B & C	M.D.	Cathode ray tubes. Replaced by 325-A, B, and C and 326-A, B and C tubes, all of which were discontinued prior to 1942.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

Western Electric Company
Radio Division
Department 9715

October 14, 1946
Page 19 of 86 Pages

Confidential - Bell & Commercial Electron Tubes
For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
225-A	M.D.	Triode.		
226-A	M.D.	Rectifier.		
227-A		Code number in our series but not our tube. Listed in the W.P.B. pamphlet "Scheduled Producers of Electron Tubes" with Eitel McCullagh as manufacturer.	Eitel McCullagh	
228-A	L	Filamentary water cooled triode 5 KW three element broadcasting tube. 6-B Transmitter and its predecessors. About 40 sockets in use 4/1/45. Government says use in place of Federal F-328-A - 2/1/45.	Amperex Federal	328-A
229-D	M.D.	Triode.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 20 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
230-D	M.D.	Same as 231-D except for base, which is old UV type.		
231-D	S	Small, filamentary triode with low filament power consumption. 309-A Police Radio Transmitting Equipment. 32-A and 55-A Amplifiers, 6044-A Test Sets, 4-A P.A. System, 11-A and 12-A Oscillator, 20-A Control Unit; 701-A Oscillator in 276-A Panel. (Merchandise Control.)		UX-199 (obsolete)
232-A	L	Water cooled triode. 7-A and 306-A Transmitters. Replaced by 232-B but since conversions are not being made smoothly, consider as A & M only.		
232-B	L	Filamentary water cooled triode 25 KW. Redesignated 232-A. Replaces 232-A but connectors have to be changed as follows: One Det. 5-A ESO-602410 in D-85491 and D-95289 Second Power Amplifier Units of the 7-A Transmitter; one Det. 7 ESO-602079 in 306-A Equipments; two Det. 3-A ESO-608894 in 306-B Equipments; and six Det. 1-A ESO-608894 in the D-85493 and D-95290 Third Power Amplifier Tube Units of the 7-A Transmitters and 306-A and 306-B - 50 KW Equipments. Still used in 50 KW Equipments. 342-A can replace this tube in existing sockets. Optional in place of 342-A tubes in 406 and 407 types R.T.E.	Federal R.C.A.	F-332-C 893*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 21 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

CHARACTERISTIC DATE

<u>Code</u> <u>Number</u>	<u>Price</u> <u>Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
232-BA	L	Standards of good Engineering Practice lists this number for a 232-B with fins for air cooling. H.E. Mendenhall reserved the code number in 1941 when we were active on a 10 KW air cooled AM Transmitter but the only work done by Mr. West was procuring a tool for fins somewhat longer than the fins used on other tubes. No tubes manufactured to date -3/23/46.		
233-B	L	Half wave water cooled rectifier 50 KV. Rocky Point Transoceanic (non-stock). Uses same water jacket as 222-A and 237-A.	Federal	F-333-A
234-A	M.D.	Rectifier tube for 7-A Radio Transmitter. Since old KSL Transmitter was sold to Government and converted to use the 249-B tube, KMOX has the last one in operation (1/21/45). Told Graybar, St. Louis to convince KMOX to convert (1/26/45).		
235-D	M.D.	Used in the D-88000 Amplifier.	R.C.A.	201

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 22 of 86 Pages

Belk & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code</u> <u>Number</u>	<u>Price</u> <u>Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
236-A	L	Filamentary water cooled triode 20 KW. A. T. & T. Co. (Merchandise control).		
237-A	M.D.	Half-wave, high voltage, water cooled rectifier. 7-A Transmitter. 237-A replaced by 344-A tube. Uses same water jacket as 222-A and 233-A.	Federal	F-337-A F-237-A
238-A	M.D.	Alkali metal photoelectric cell gas filled for use in film reproduction equipment. Coded 4-A PEC - also Manufacture discontinued.		
239-A	M.D.	For use in 710-A Control Cabinet. Replaced by 264-C.		
240-B	L	Filamentary water cooled triode 10 KW. Replaces 240-A. Long Lines, Short Wave, Transoceanic and Ship-to-Shore Radio Transmitter.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued.
(*) With modifications.

(L) Large value.

CHARACTERISTIC DATE

Western Electric Company,
Radio Division
Department 9715

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

September 10, 1946
Page 23 of 86 Pages

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
241-B	M	Filamentary air cooled triode 275 W. Long Lines - D-90643 Short Wave Transmitter. (A replaced by B.) 405 and 407 Trans. Eqpts. Replaced by 357-B in new RTE's.	G. E. Westinghouse	GL-849* WL-849*
242-C	S	Filamentary air cooled triode 100 W. Replaces A and B and also 211-D. Has Molybdenum plate originally designed for sound pictures and amateur use. Used in D-90684 Broadcast Amplifier, 5-C, 6-B, 7-A Transmitters and 309-A (Police) Radio Transmitting Equipment. 20-A and 23-A Radio Transmitter. (D-98653 Oscillator Modulator unit modified 12-B Transmitter. Used in short wave stations. 450-A1 and 451-A1 (100 and 250 W) RTE. Substitute for 214-E after strapping plate and grid terminals in 60-B Rectifier socket. Altec uses 1500 yearly (8/23/45).	G. E. R. C. A. Westinghouse	GL-242-C 211* WL-211*
243-A	M.D.	Triode.		
244-A	S	Low power triode with indirectly heated cathode. Used in 9-A, 9-B, 9-D, 11-A, 11-B, 11-C, 12-A, 13-A and D-94207 Receivers. D-93315 Transoceanic Receiver. 60-A, 78-A, 78-B, 83-A, 83-B, 83-C, 84-A and 85-A Amplifiers. 256-A and 257-A Panels. B-2 Privacy Equipment; Component Part Apparatus - 75-A 77-A, 75-B, 77-B Amplifiers. 20-A Radio Transmitters. D-156000 Radio Transmitter. Station WMIN reported long life in the feedback rectifier circuit operated at .8 ma.	R. C. A.	56

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 24 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
245-A	S	Voltage amplifier tetrode with indirectly heated cathode. Used in 9-A, 9-B, 9-D, 13-A Receivers. 83-A, 83-B, 83-C, 83-D, 83-E and 83-F Amplifiers. D-93315 Transoceanic Receiver.	R. C. A.	24-A*
246-A	S	Voltage amplifier filamentary tetrode. Used in D-90303, D-90848 and D-91719 Transoceanic Receivers. Short wave receiving sets. (Merchandise control.)	R. C. A.	22
247-A	S	Low power triode with indirectly heated cathode. Used in 10-A Receiver. 15-A, 16-A and 23-A Radio Transmitters. 61-A Amplifier. 242-A, 243-A and D-96662 Panels. 20-A Radio Transmitters. 702-A Oscillator. New 405 and 407 Trans. Equipments. 443-A1 (1 KW) R.T.E. 451 Type R.T.E.		
248-A	M.D.	Triode.		
249-B	S	Half wave mercury vapor rectifier. Replaces 249-A tube. 15-A and 16-A Transmitters, Navy Aircraft Radio Transmitting Equipment. 71-B, 87-A, B and D, 88-A and 90-A Amplifiers. 309-A Police R.T.E. 2-A, 2-B, 4-A, 9-A and 9-B Rectifier. D-96959 Panel. 20-A and 23-A Radio Transmitters. 50 KW Equipment. 405 and 407 Trans. Epts. used by E.R.P. 443-A1 (1 KW) R.T.E. 430-B1 (100 Watt) R.T.E. FM Transmitters. (Our tube compares unfavorably with competition). The same tube with a two prong base is coded 258-B.	Field Taylor	866* 249-B

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 25 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
249-C	S	D-96656 R.T.E. Navy. Navy using Raytheon on Plane Jobs. D-97502 Rectifier. D-97500 General Announcing systems. Same size envelope as 249-B but larger anode cap. D-97600 Flight Deck Announcing System (40 each) C0-118487 reduces size to permit aero-plane use - 6/3/35. 14-A Rectifier. 99-A and 100-A Amplifier.	Taylor	
251-A	L	Filamentary air cooled triode 1KW. 9-A, 9-B, 14-A Transmitters. D-94723 Transoceanic Transmitter. 71-A & B, 88-A, 90-A Amplifiers (500 Watt); 303-A R.T.E.	G. E. Westinghouse	GL-851* WL-851*
252-A	S	Moderate power, filamentary triode. Used in 57-A, 59-A, 59-B and 67-A Amplifiers. 10-A, 11-A, 15-A and 16-A Radio Transmitters. D-96656 R.T.E. Navy, 309-A Police R.T.E. D-96662 Panel.		
253-A	S	Half wave, mercury vapor rectifier. Used in 57-A 59-A, 59-B, 67-A, 71-A and 6071-A Amplifiers; 10-A Transmitters; 10-A Rectifier; 223-A and D-87587 Panels; 9-A Speech Input Equipment; 302-A, 303-A, 304-A, 308-A Radio Trans. Equipments. Sound Picture Equipment. Also used with adapters in 6000-A Rectifier in place of 211 Tube.	Westinghouse	WL-866A/866
254-A	M	Filamentary air cooled tetrode. Used in 10-A (Aviation) and D-93258 Radio Transmitter.	Westinghouse	WL-865*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 26 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
254-B	M	Filamentary air cooled tetrode. Does not replace 254-A Tube. (7-1/2 volt instead of 5 volt, etc.) Used in D-93258 and D-94723 Transoceanic Transmitters. Airport Transmitters.	R. C. A. G. E. Westinghouse	8001* GL-865* WL-865*
255-B	M	High voltage 20 KV air cooled half wave mercury vapor rectifier. Replaces 255-A Tube. Transoceanic Transmitters, D-96847 (5000 Watt) Amplifier (six tubes per). 407-A Radio Trans. Eqpt. (6 each). (6) D-158974 Amp. Transoceanic. (6) 50 KW FM Transmitter.	G. E. Westinghouse R. C. A. Federal	GL-869-B* 869-B* 869* F-369-A*
256-A	S	Three element thyratron with indirectly heated cathode. 1-A Photomatic Equipment. (We are out of business on this equipment.) Flight Deck Announcing System. D-91818 Oscillograph 209-A Radio Telephone Equipment.	R. C. A.	885*
257-A	S	Small filamentary triode used extensively by Bell System. Low filament power consumption. Double-ended 231-D.		
(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value. (*) With modifications.				

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 27 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
258-B	S	Half wave, mercury vapor rectifier. Used in 12-A Radio Transmitters; 302-A, 303-A, 304-A and 306-A Radio Transmitting Equipment; D-94723 Transoceanic Transmitter; 6071-A and 71-A Amplifier; D-87587 Panel. (D-98653 Oscillator Modulator unit modified 12-B Transmitter.) Same as 249-B except has two prong base.	G. E. Taylor	866-A/866* 258-B
259-A	S	Voltage amplifier, tetrode with indirectly heated cathode. Used in 10-A, 11-A, 11-B, 11-C, 12-A, D-94207 Receivers; 234-A and 236-A Panels; 1-A and B Frequency Monitoring Unit; Component part apparatus 75-A, 75-B, 77-A and 78-B Amplifiers. 2-A Phase Monitor. D-156000 Radio Transmitter. Partially replaced by 283-A. Has Higher trans-conductance than R.C.A. 24-A or W.E. 245-A.	R. C. A.	35-A
259-B	S	Voltage amplifier tetrode with indirectly heated cathode. Does not replace 259-A Tube. Exceptionally low noise. Laboratory, college and experimental uses.		
260-A	M.D.	Filamentary air cooled tetrode. D-93259 and D-94723 Transoceanic Transmitters. Ship-to-Shore. We have used R.C.A. tubes since 1939.	R. C. A. G. E. Westinghouse	860 GL-860 WL-860

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 28 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
261-A	M.D.	Filamentary air cooled triode. Used in 8-A, 8-B, 9-A, 9-B and 9-C Transmitters. Replaced by 276-A. (242-C would be overloaded.)	G. E. Westinghouse R. C. A.	GL-835* WL-680* 211*
262-B	S	Low power triode with indirectly heated cathode. Replaces 262-A Tube (if heater-cathode exceeds 30 volts, use R.C.A. 1603), which was called a quiet tube for amplification of small low frequency signals (SPD-4) until R.C.A. brought out their 1603 which is really quiet. Used in 59-A, 59-B, 62-A, 63-A, 67-A, 69-A, 70-A, 80-A, 80-B, 81-A, 82-A, 86-B, 86-D, 92-D, D-94531, D-95159 & D-95508 Amplifiers. D-96656 R.T.E. Navy. Navy Precision Clock. 309-A Police R.T.E. IG & 700-A Volume Indicator. 15-A & 23-A Transmitter. 249-A Panel. 9-A & 15-A Speech Input Equipment. D-97600 Flight Deck Announcing System (10 each). 703-A Oscillator. D-99015 Recording Reproducing System. For use with 105-A, 106-A & 104-A Amplifiers (Speech Input) used by E.R.P. (about 5500 yearly). (6) D-99945 Transoceanic Receiver. D-156000 Transmitter.	R. C. A.	1603

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 29 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
263-B	S	Full wave thermionic mercury vapor rectifier. Replaces 263-A Tube. D-94723 Transoceanic Transmitter and 5-A Current Supply Set. Used in Rectifiers in Aircraft Radio Transmitters. (United Air Lines). Holdaway says the Electron Co. EL6CF or 4B25 can be used as substitutes with a base change - 7/25/45. ERP West Coast has 20 sockets in operation requiring 100 tubes annually. M.D. rating is under consideration 1/1/46.	Electron Continental " Westinghouse	EL6CF* 4B25* CE-221* WL-670A*
264-C	S	Small low noise filamentary triode. Replaces 264-A and B. ERP use most of our production in 47-C, 47-D, 48-B, 49-C, 53-C, 53-D Amplifiers. 710-B Central Cabinet. D-90191 Panel. 70-B1 Telephoto System.	Amperex R. C. A.	264-B 864
265-A	M.D.	Triode.		
266-B	L	Half wave mercury vapor rectifier 22 KV. Replaces 266-A. 306-A Radio Transmitting Equipment.	Westinghouse G. E. Amperex Federal	WL-266-B GL-266-B 266-B F-266-A
266-C	L	Same as B, except that the terminals correspond to those of our competitors. Originally intended for sale to composite stations.	Westinghouse G. E. Amperex	WL-857-B GL-857-B

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 29 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
263-B	S	Full wave thermionic mercury vapor rectifier. Replaces 263-A Tube. D-94723 Transoceanic Transmitter and 5-A Current Supply Set. Used in Rectifiers in Aircraft Radio Transmitters. (United Air Lines). Holdaway says the Electron Co. EL6CF or 4B25 can be used as substitutes with a base change - 7/25/45. ERP West Coast has 20 sockets in operation requiring 100 tubes annually. M.D. rating is under consideration 1/1/46.	Electron Continental "Westinghouse	EL6CF* 4B25* CE-221* WL-670A*
264-C	S	Small low noise filamentary triode. Replaces 264-A and B. ERP use most of our production in 47-C, 47-D, 48-B, 49-C, 53-C, 53-D Amplifiers. 710-B Central Cabinet. D-90191 Panel. 70-B1 Telephoto System.	Amperex R. C. A.	264-B 864
265-A	M.D.	Triode.		
266-B	L	Half wave mercury vapor rectifier 22 KV. Replaces 266-A. 306-A Radio Transmitting Equipment.	Westinghouse G. E. Amperex Federal	WL-266-B GL-266-B 266-B F-266-A
266-C	L	Same as B, except that the terminals correspond to those of our competitors. Originally intended for sale to composite stations.	Westinghouse G. E. Amperex	WL-857-B GL-857-B

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

September 10, 1946
Page 30 of 86 Pages

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
267-B	S	Half wave mercury vapor rectifier. Replaces 267-A. 443-A1 (1 kw) R.T.E. D-158974 Amplifier Transoceanic (6) D-156000 SSB R. Trans. D-94723 Transoceanic Transmitter. D-95857 Set of Parts. (See 319-A for 4 prong instead of 2 prong based tube.) D-95858 Rectifier.	Westinghouse G. E.	872-A/872* GL-872-A*
268-A	M	Filamentary air cooled triode 25W. 10A Transmitter (old airport job).		
269-A	S	Three element filamentary thyatron. Mdse. Control.		
270-A	L	Filamentary air cooled triode 350 W. 71-A and B, 90-A and 6071-A Amplifier. (250 Watt.) 302-A R.T.E. 212-E has been substituted in practically all 71 Type amplifiers.	Amperex G. E.	GL-849*

(S) Small value. (M) Medium value. (W.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 31 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
271-A	S	Moderate power triode with indirectly heated cathode. Used in 700-A and B Oscillators. 12-A, 15-A, 20-A and 23-A Radio Transmitters. 306-A and 309-A Police Radio Transmitter Eqpt. 78-A, 78-B and 82-A Amplifiers. 1-A and B Frequency Monitoring Unit. 233-A and 234-A Panels. D-94768, D-94996, D-94997, D-94998, D-95001, D-95006 and D-95007 Sets of Parts. 302-A, 303-A and 304-A R.T.E. 15-A Speech Input Equipment. Modified 42 type amplifier in Sound Picture Recording.	R. C. A.	801* 843*
272-A	S	Low power triode with indirectly heated cathode. 14-B Radio Transmitting Equipment. 74-A and D-93679 Amplifiers. 9-A and B Rectifier. Navy Precision Clock - 16-A Radio Receiver. 6001-A Radio Compass. D-97600 Flight Deck Announcing System (8) each). 282-A Panel. (1) D-99945 Transoceanic Receiver.		
273-A	-	Command Set. Program Distribution. Tel. Companies (Demand small). Apparently no sockets in the field and shop prefers not to make.		
(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value. (*) With modifications.				

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 32 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
274-A	S	Full wave filamentary high vacuum rectifier. 1-A Frequency Monitoring Unit. 11-A, 11-B, 11-C, 13-A and D-94207 Receivers. 5-A, 6-A, 7-A, 7-B, 7-C, 8-A and D-97503 Rectifiers. 78-A, 78-B, 85-A, 86-A, 86-B, 86-D, 91-A, 92-A, 100-A, D-94531, D-95159 and D-95508 Amplifiers. 309-A Police R.T.E. 15-A Speech Input Equipment. D-97500 General Announcing Systems (2 each). D-97600 Flight Deck Announcing System (24 each). 20-A and 21 Type Police Radio Transmitters. 280-A Panel. 282-A Panel. 703-A Oscillator. 405 and 407 Trans. Eqpt. 2-A Phase Monitors. Used by ERP. (6) D-99945 Transoceanic Receiver (3) D-156000 Radio Transmitters. If load is not over 120 mls., R.C.A. 80 can be used interchangeably.	R. C. A.	80* 523*
274-B	S	Same as 274-A except 274B has an octal base. Designed for use in 124-A Amplifier (1). Approximately 9935 sockets in Gov't. Radio & Radar gear of W.E. mfr. - 5/1/45.	R.C.A. Sylvania	5Y3G*
275-A	S	Moderate power filamentary triode. 11-A, 11-B, 11-C, 13-A and D-94207 Receivers. 85-A, D-94531 and D-95036 (S.P.), D-95159, D-95508 Amplifiers. 7-A, 7-B, 7-C Rectifiers. D-96656 R.T.E. Navy. D-97600 Flight Deck Announcing System (4) each. 280-A Panel. 282-A Panel. About 20 sockets in Gov't. Radio & Radar gear of W.E. mfr. - 5/1/45. (House control)		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 33 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
276-A	S	Filamentary air cooled triode 100 W. 306-A Radio Transmitting Equipment. D-96656 R.T.E. Navy. Replaces 261-A and 248-A Tubes. Used in Aircraft Transmitter in place of 211-D and E.	G. E. R. C. A.	GL-276-A 211*
277-A	S	Three element thyratron with indirectly heated cathode. 12-A Radio Transmitter. 302-A, 303-A, 304-A and 306-A Radio Transmitting Eqpt. 1-A Frequency Monitoring Unit. All sets of parts listed under 271-A. Entirely replaced by 287-A, except special use by B.T.L. If equipment now uses 277-A, customer will need a D-95076 Adapter to convert to 287-A if he hasn't done so already.		
278-A	M.D.	Filamentary air cooled tetrode. Screen grid 251-A. Used by B.T.L. and A.T. & T. for experiments, also at Rugby Eng. - Transoceanic. Not stocked. Made only in BTL and abandoned about 1935. Use 379-A or 251-A and neutralize.		
279-A	L	Filamentary air cooled triode 1200 W. 71-A and B, 90-A and 6071-A Amplifiers. (1000 Watt). 304-A Radio Transmitting Equipment. D-96847 Amplifier. (2) D-156000 Radio Trans. Replaced by 379-A Tube in all but D-156000 R.T. About 220 sockets in field to maintain - 1/15/46.	Westinghouse G.E.	WL-851* GL-851*

{S} Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
{*} With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 34 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
280-A	M.D.	Half wave thermionic mercury vapor rectifier. D-94704, D-94706 and D-94887 General Announcing Systems. Amplifier failed - now has no specific use. (Stock junked in 1938.)		
281-A	S	Moderate power filamentary coplanar-grid tetrode. 1-A Telephotographic Equipment. (Assoc. Press).		
282-A	M	Filamentary air cooled tetrode 70 W. 308-A and 309-A (Special in 16-A). Police R.T.E. 208-C and 209-A Radio Telephone Equipment. Airlines are purchasing tubes from other sources. (Taylor) Replaces 282-B since modified.	Taylor	282-A
282-B	M.D.	Filamentary air cooled tetrode. 282-A with isolantite base, heavier filament, better support. Slightly different characteristics which show up in Airplane Circuits. D-96656 R.T.E. Navy. Patrol Planes. Observation and Scout Planes. Replaced by 282-A Tube since modified.		
283-A	S	Variable-mu voltage amplifier, tetrode with indirectly heated cathode. Partially replaces 259-A. 9, 10, 11 and 12 Type Receivers. D-96530 Receivers. 208-C Radio Telephone Equipment. 2-A Phase Monitor.		

{S} Small value. (M) Medium Value. (M.D.) Manufacture discontinued. (L) Large value.
{*} With modifications.

CHARACTERISTIC DATE

Western Electric Company,
Radio Division
Department 9715

September 10, 1946
Page 35 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
284-D	S	Filamentary air cooled triode 85 W. Replaces 284-A, B & C. 9-A and B Rectifier. Replaces 280-A in General Announcing Systems. 16-A Police Radio Transmitter. D-96662 Panel. D-97600 Flight Deck Announcing System. (16 each) U. S. Navy. D-97501 Amplifier. D-97500 General Announcing System (4 each). 87-A, B and D and 99-A Amplifier. About 500 yearly used by E.R.P.	Westinghouse G. E. R. C. A.	WL-845* GL-845* 845*
285-A	S	Lower power pentode with indirectly heated cathode. 12 Type Radio Receiver. D-96530 Receiver. 208-C Radio Telephone Equipment.	R.C.A.	38* 41*
286-A	S	Variable- μ , voltage amplifier, pentode with indirectly heated cathode. 13-A and B Radio Receiver DSB (256-A Panel). Navy Direction Finder. 82-A, 83-A, 83-B, 83-C and 84-A Amplifiers. Trucksess estimates 2000 for regulated rectifiers in 1947 - 3/31/46.		
287-A	S	Three element thyratron. Replaces (partially) the 277-A by using D-95076 Adapter. 1-A Telephotographic Equipment. 12-A Radio Transmitter. D-97600 Flight Deck Announcing System (8 each). Used with all 700 Type Oscillators (about 600 sockets). (D-98653 Oscillator Modulator Unit modified 12-B Transmitter). Long Life Tube. Not used in 400 series of R.T.E.	Continental	302

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 36 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
288-A	M.D.	Half wave, tungsten filament, argon filled rectifier. To replace GE Tungar Rectifier Bulb 189048.	G. E.	189048 4B28
289-A	M.D.	Half wave tungsten filament argon filled rectifier. To replace GE Tungar Rectifier Bulb 189049 for Telephone Plant Work. Merchandise Control. Current Army - Navy #4B26.	G. E. R. C. A. Westinghouse Allen Continental JAN	189049 2000 289416-D F-60 CE-226 4B26
290-A	A&M	Variable- μ Pentode with indirectly heated cathode. 12-B, 12-C, 14-A, 16-A Radio Receiver with 6001-A Radio Compass. 208-C and 209-A Radio Telephone Equipment. 280-A Panel. E.R.P. uses. Test sets in Works and Transoceanic Telephone. (Merchandise Control).		
291-A	A&M	Pentagrid converter with indirectly heated cathode. 12-B, 12-C, 14-A, 16-A Radio Receiver with 6001-A Radio Compass. 208-C and 209-A Radio Telephone Equipment. Used in Tel. Test Sets. (6-A-7 can be rebased to make equivalent of 291-A.) (Merchandise Control.)	R. C. A.	6-A-7*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 37 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
292-A	M.D.	Duplex-Diode Triode with indirectly heated cathode. Replaced by 352-A. 12-B, 12-C, 14-A, 16-A Radio Receiver with 6001-A Radio Compass. 208-C and 209-A Radio Telephone Equipment. E.R.P. uses. Suggest substitute 352-A; only difference is in diode plate 1P, 292-A limits are 3.7 - 6.7 and 352-A limits are 4.4 - 8.0, but Stafford says 99% of 352-A production is also within limits of 292-A (6/22/44).		
293-A	S	Pentode with indirectly heated cathode. 12-B, 12-C, 13-A, 14-A, 16-A Radio Receiver with 6001-A Radio Compass. Navy Precision Clock. 208-C and 209-A Radio Telephone Equipment. 20-A Radio Transmitter. 280-A Broadcasting Panel. D-99945 SSB Radio Receiver.		
294-A	A&M	Power Amplifier Pentode. Radio or Audio Frequency for Navy. Used by E.R.P. in recorders. 100-A Recorder. Tube Shop can't meet test and there is no known substitute (1/1/45).		
295-A	S	Filamentary air cooled triode 100W. Competitive in composite Broadcasting Stations. 405-A Radio Equipment Feedback Circuit. D-99762 Conversion Parts (9 sets sold). 355-E1 R.T.E.	R.C.A. Westinghouse G. E. Continental	203-A WL-203-A GL-203-A C-203-A

{S} Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
{*} With modifications.

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 38 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
296-A	M.D.	Comparable to R.C.A. 849 (Carbon plate 270). Cancelled.	R. C. A.	849
297-A	S	Three element filamentary Thyatron. Used for testing protection circuit of 1-A Thermostat (Aviation) also in test circuits in B.T.L. considered as a telephone tube. (Merchandise Control.)		
298-A	L	Water cooled triode 100 KW used as an oscillator modulator or amplifier at high power levels. Four KS-8080 Gaskets with each tube. 50 KW Non-Western and W. E. Co. 407-A (50 KW) Trans.	Federal Amperex G. E. R. C. A.	298-A 220-C* 862* 862*
298-B	L	Similar to 298A except for higher amplification factor. Used in electronic heating applications.	G. E.	862*
299-A	-	Rectifier goes with 320-A. (None authorized to date)	R. C. A.	870*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 39 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
300-A	S	Moderate power filamentary triode. Used in ten frequency 27-A Trans. 86-A, 86-B, 86-D, 87-A, 91-A and 92-A Amplifiers. Also D-95036 Amplifiers converted by E.R.P. D-97600 Flight Deck Announcing System (8 each). Teleflash, Amateur use. Replaced by 300-B.	R. C. A.	250*
300-B	S	Same as 300-A Tube except for location of bayonet pin in base. For use by E.R.P. in 42 and 46 Type Amplifiers. Replaces some 205-D and all 300-A Tubes. Bayonet pin was changed so the 300-B could be used in old 205-D sockets. Since the 300-A was always used in wafer sockets, the 300-B is interchangeable. About 3481 sockets in Gov't Radio and Radar gear of W. E. Manufacture - 5/1/45.	R. C. A.	2A3*
301-A	S	Full wave mercury vapor Rectifier. 71-B and 90-A Amplifiers. 12-A Rectifier. 280-A Panel. 443-A1 R.T.E. New 1-3-10-50 KW FM Transmitters.	R. C. A. R. C. A. G. E.	2866-A* 83* GL-2866-A*
302-A	M.D.	Oscillograph. Direction Finder, U.S. Navy. Replaced by 324-A Tube.		
(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value. (*) With modifications.				

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 40 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
303-A	S	Duo diode triode with indirectly heated cathode. Similar to 292-A. D-96530 (modified 12-D) Receiver. 13-R Receiver (SSB). 208-C Radio Telephone Equipment.		
304-A	M. D.	Filamentary air cooled triode. Short wave. Carbon plate. Westinghouse used in short wave transmitters. Also amateur field. Replaced by 304-B.	Federal G. E. Westinghouse	204-A GL-204-A WL-204-A
304-B	M.D.	Filamentary air cooled triode. Used at full rating at frequencies up to 100 mc. and at reduced power to 300 mc. (Molybdenum plate 304.) Replaces 304-A. Government use. (2) D-158974 Amplifiers. Manufacture discontinued in 1941. (316-A more or less took its place in any new developments.)	R. C. A. Raytheon G. E.	834 RK-32 GL-834
305-A	S	Filamentary tetrode 60 W. Navy Direction Finder. Remote Radio Key Equipment, Navy. 16-A Police Radio Transmitter. D-96657 Panel. Amateur use.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 41 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
306-A	S	Moderate power filamentary pentode. 16, 17, 18 and 21 Types Police Radio Transmitters. D-96657 Panel. (Amateur use.) (Subcontracted to National Union in 1944 but they will make only substantial quantities.)	National Union	306-A
307-A	S	Moderate power filamentary pentode for use in 19-A Radio Transmitter. (Itinerant Flyer.) 20-A Radio Transmitter. Amateur use. Special 14 Type Transmitter for Signal Corps. Ten frequency 27-A Radio Transmitter (Aviation).	Raytheon Sylvania Ken-Rad Nat'l. Union	75* 307-A
308-B	M	Filamentary air cooled triode. 250 W. D-97600 Flight Deck Announcing System (32 each). For use in high power audio frequency amplifier in announcing system.		
309-A	S	Voltage amplifier variable mu pentode with indirect heating cathode. For use in RA - 150 Amplifier (ERP) (4 each). (Merchandise control.)		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 42 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
310-A	S	Voltage amplifier cathode type pentode. Inexpensive Theatre Equipment. Coaxial Cable Job - 91-A, 92-A Amplifier. "J" & "K" Carrier Systems at regulated battery offices. A1 Noise Reducer. 405, 406 and 407 & 355-EI-R.T.E. (1) D-99945 Radio Receiver. Transoceanic (SSB). D-99762 Conversion Parts. (Merchandise Control.)		
310-B	S	Voltage amplifier pentode with indirectly heated cathode. Used in Speech Input Equipments. Used by E.R.P. Supposed to be extremely free of noise but has proven inferior to R.C.A. 1603 in meeting FM noise requirements.	R. C. A.	1603
311-A	S	Low power cathode type pentode. Carrier Telephone Systems. D-156000 Radio Trans. (Merchandise Control.)	R. C. A.	6K6
312-A	M	Filamentary air cooled pentode 50 W. 601 and 602 and GN Equipment. V-2-A in 451-A R.T.E. Used in 450-A R.T.E.	General Electronics R. C. A. Raytheon G. E.	38412 804* RK-20-A* GL-813/814

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 43 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
313-C	S	Three element cold cathode. Subset of the four battery selective ringing, Chicago. 50 KW Eqp't. 405 and 407 Radio Receiver. (SSB) Replaces 313-A Tube. About 1700 sockets in Gov't. Radio & Radar gear of W.E. mfr. - 5/1/45. (Merchandise Control.)	United Elec.	CV-75*
313-CA	S	Three element cold cathode. Replaces 313-AA. Specially selected 313-CC tubes. The 313-CC can be substituted for all known uses except socket GD of A-1 vogad. (SSB). Gov't. Contract Service estimates about 5100 sockets in special Gov't. gear - 5/1/45. (Merchandise Control.)		
313-CB	S	Three element cold cathode. Same as 313-C except has higher main-gap voltage. Used in telephone equipment. (Merchandise Control.)		
313-CC	S	Three element cold cathode. Used in D-99945 Receiver (SSB) also R-1 and R-2 of A-1 Vogad. (SSB). About 1200 sockets in special Gov't. gear - 5/1/45.		
313-CD	S	Three element cold cathode. Used as indicator in test circuit for X-66031 Repeater. Has paint removed from an area at the end of the bulb for observation.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 44 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
314-A	S	Full wave mercury vapor rectifier. Inexpensive theatre equipment. 12-A and B Rectifier. 101-A Amplifier.	G. E.	
315-A	M	Half-wave mercury vapor rectifier 12.5 KV. D-96847 R.T.E. 405 Radio Trans. Equipment.	Federal G. E. Amperex	315-A
316-A	S	Filamentary air-cooled triode (door knob). Amateur use. Frequency limit of 750 mc. Leads are designated TP-5157 (4 required). Boeing adopted for their transmitter in the Clippers about 1943. Used by Alaska Communications. General Radio uses in frequency meter.	Tungsol G. E.	GL-316-A
318-A	S	Heater type pentode. Originally designed for 50 KW equipment but R.C.A. 837 being used in present circuits. D-99110 (100 W.) Transmitter and 23-A Transmitter.	G. E. R. C. A.	GL-837

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Elec c Company
Radio Division
Department 9715

October 14, 1946
Page 45 of 86 Pages

Bell & Commercial Electron Tubes Confidential - For Distribution Only Within the Company

Code Number	Price Category	Description & Material in Which Used	Competition	Code
319-A	S	Half wave mercury vapor rectifier similar to 267-B except for four prong instead of two prong base. Composite stations.	Westinghouse G. E. R. C. A. Federal Raytheon	WL-872-A/872* GL-872-A 872-A 353-A* 872-A
320-A	L	Water cooled triode. 250 KW. For 500 KW Transmitters.		
321-A	M	Half wave mercury vapor rectifier similar to 315-A except four prong instead of two prong base. Composite and competitive stations. The 321-A has higher inverse peak than competitive tubes.	(See 319-A)	
322-A	M	Filamentary air cooled pentode. 125 W. for use in ten frequency 27-A and 27-AA Radio Transmitters.	Westinghouse G. E. R. C. A. Raytheon	WL-803 GL-803 803 28-A*
323-B	S	Three element thyatron. Entirely replaces 323-A. Has somewhat higher ratings and uses two more standard parts. Used for charging P.B.X. and Central Office batteries. See 393-A. B. T. L. estimates (5/31/46) 4200 will be needed in 1947 for regulated rectifiers. (Merchandise Control.)	Continental	

{S} Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
{*} With modifications.

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 46 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
324-A	M.D.	Two element half wave rectifier for use with 325, 326 and 330 type oscillograph tubes for high voltage low current. Designed to replace D-96413 Tube and 302-A Tube. Discontinued 3/13/24.		
325-A, B-C	M.D.	High vacuum cathode ray Oscillograph tube. Replaces 224-C Tube. (A-Green fluorescent screen of about 4-1/2" diameter, medium persistence) (B-Long persistence screen of high fluorescent intensity) (C-Blue fluorescent screen of highly actinic quality). (See 326-A, B, C below).		
326-A, B-C	M.D.	High vacuum cathode ray Oscillograph tube. Replaces 224-C Tube. (A-Medium persistence screen of green fluorescent) (B-Long persistence screen) (C-Blue fluorescent screen highly actinic). Discontinued at the beginning of the War. Navy got Allan B. Dumont Lab. in Passaic to manufacture under our number as a stop gap.		
327-A	M.D.	Two element Argon filled rectifier tube having a tungsten filament for charging battery equipment in telephone plants. Replaced by GE Cat. 12X825 tungar. (Merchandise control.)	JAN G.E. Westinghouse Eitel McCullogh	4B35 12X825 WL-966626
(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (*) With modifications.			(L) Large value.	

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

September 10, 1946
Page 47 of 86 Pages

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
328-A	S	Voltage amplifier pentode with indirectly heated cathode used in carrier repeaters and audio frequency amplifiers. (Merchandise control.)	Federal	328-A
329-A	S	Lower power cathode type pentode. Power output tube used in connection with carrier telephone systems in non-regulated battery offices. (Merchandise control.)		
330-A B-C	M.D.	Three trace Oscillograph tubes developed for college use. 330-A Green fluorescent screen of medium persistence 330-B long persistence screen of high fluorescent intensity 330-C blue fluorescent screen of high actinic quality.		
331-A	S	Filamentary air cooled triode. 125 W. To be used in last audio stage of aircraft radio transmitter. 443-A1 (1 kW) R.T.E. 430-B1 (100 watt) R.T.E. About 864 sockets in Special Gov't. gear 5/1/45.	G. E. Westinghouse R. C. A. United Elec. Raytheon	GL-805 WL-805 805 905 57

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

Western Electric Company
Radio Division
Department 9715

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

September 10, 1946
Page 48 of 86 Pages

CHARACTERISTIC DATE

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which</u>	<u>Competition</u>	<u>Code</u>
332-A	M	Filamentary air cooled pentode. It is intended for use in single side band and multiple steering antenna radio system. D-156000 Radio Transmitter. Similar to 322-A Tube.	G. E. Westinghouse	GL-803* WL-803*
333-A	S	Three element cold cathode used in subscriber sets and is the same electrically as the 313-C Tube. (Merchandise Control.)		
334-A	M.D.	Mercury vapor thyratron. Rectifier in battery charging equipment in telephone plants. Replaced by 354-A in most cases. (Merchandise Control.)		
335-A	M.D.	Same as 334-A except with argon gas in addition to mercury vapor. Same use as 334-A. Replaced by 354-A Tube. (Merchandise control.)		
336-A	S	Power amplifier pentode. Audio amplifiers and Speech Input Equipments. Used by E.R.P. 106 Amplifier (1 each).		
(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value. (*) With modifications.				

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 49 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
337-A	S	Variable MU pentode with indirectly heated cathode. For use in new single side band and MUSA Receivers. D-99945 Radio Rec. (SSB) D-156000 Radio Transmitter. (Merchandise Control.)		
338-A	S	Three element thyratron with indirectly heated cathode for use in carrier telephone systems. (Merchandise control.)	R. C. A. Westinghouse	885* WL-629*
339-A	S	Filamentary pentode. Designed for use in 24-A Radio Transmitter. 221-A R.T.E. (emergency set for A.T. & T.) and 224-C R.T.E. (Ship to shore). Used by Coast Guard, Signal Corps (Alaska link) A.T. & T. and Harborecraft.		
340-A	L	Three element water cooled tube designed for use as an oscillator modulator or amplifier at the higher power levels. Short wave broadcasting equipment and also transmitters developed for the A. T. & T. Co. Long Lines Dept. Similar to 342-A tube except designed for use at higher frequencies. (4) D-158974 Amplifier Transoceanic.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 50 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

Code Number	Price Category	Description & Material in Which Used	Competition	Code
341-A	L	Water cooled triode primarily used in second power amplifier of transmitters already in the field. Same as 232-B except that it operates at a filament current of 40 amperes instead of 60 amperes.		
341-AA	L	Previously known as Spl. Low hu. 343-AA - designed for use in Transmitter of WQXR and other composite 5 or 10 kw Radio Transmitting Eqpts. as an audio frequency amplifier and modulator at the higher power levels. Forced air cooled 3 element tube, filament voltage 21.5 V. Filament current 57.5 amp. Made 10 for WQXR. Extremely long life. WQXR returned one of original five for fln credit after 22,000 hours of service.	G. E. Westinghouse	GL-891-R WL-891-R
342-A	L	Water cooled triode similar to 232-B except that it employs a filament operating at 70 amperes instead of 60 amperes to improve the tube life. Supersedes the 232-B for new applications. Used in the third power amp. of the 407-A1 (50 KW) Trans. Works better than Federal F-332-C (says Navy). Inherently noisier than the 232-B and is unsatisfactory as a replacement in 50 KW Transmitters.	Federal Amperex R. C. A.	332-C 232-CH* 893*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 51 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
343-A	L	Water cooled triode similar to 220-B and C except that it operates at a filament current of 60 amperes instead of 40 amperes (to increase the tube life) and is inherently noisier. Supersedes the 220-B and 220-C tubes used in 405-A2 (5 KW) Transmitter but do not substitute for 220 tubes in prior models. "Super-duper" is D-170924.	Federal R. C. A. G. E. Westinghouse	343-A 892* GL-892* WL-892*
343-AA	L	Same as 343-A except equipped with fins for air blast cooling. Used in 405-B1 and B2 R.T.E.	R. C. A. G. E. Westinghouse	892-R* GL-892-R* WL-892-R*
344-A	M.D.	Water cooled rectifier similar to the 237-A tube except that it employs a filament which operates at 73 amperes instead of 60 amperes which gives the tube increased life. Designed to replace the 237-A. Not manufactured.		
345-A	S	Full wave high vacuum rectifier tube intended for use with coaxial cable rectifiers and for feedback in radio broadcast transmitters. Can be used where R.C.A. 84 or 6Z4 is specified. D-99110 OSC Amp. 405-A1 and B1. 406-A and B, 407-A1, A2, A3 and A4. Radio Transmitters. Similar to 351-A Tube. Do not use competitive tubes if load is over 60 mls.	R. C. A. R. C. A.	84 6Z4

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 52 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

Code Price
Number Category

Description & Material in Which Used

Competition

Code

346-B S

Three element cold cathode gas filled tube for use as a relay, voltage regulator or rectifier. For use in district selector circuits; remote control zone registration. (Merchandise Control)

347-A S

This tube is similar in design to 262-B tube except that it employs a 6.3 volt, .5 amperes heater and is equipped with a small octal base. For use in public address equipments. 120-A and 121-A Amplifiers. (The 1603 is quieter and will meet the FM noise requirements.)

R. C. A.

1603

348-A S

This tube is similar in design to the 310-B tube except that it employs a 6.3 volt, .5 ampere heater and is equipped with an octal base. For use in public address equipment. 430-B1 (100 watt) R.T.E., 120-A and 121-A Amplifiers. 124 type Amplifier (2) 503 FM R.T.E. (which has been changed to call for 6J7 and 6J5 Tubes). About 12 sockets in special Government gear 5/1/45.

R. C. A.

6J7
6C6*
6J5*
1603*
1620*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 53 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
349-A	S	Suppressor Grid Pentode having indirectly heated cathode intended as audio frequency power amp. This tube is similar in design to the 336-A except that it employs a 6.3 volt, 1.0 ampere heater and is equipped with an octal base. Initial use in 121-A Amplifier. (443-A1) R.T.E. 1-5-50 KW Pre-war FM Transmitter. About 1600 sockets in special Government gear 5/1/45.	R. C. A.	6F6*
350-A	S	A beam power tube similar to R.C.A. 807. Used in 443-A1 R.T.E. Amplifiers and Marine Sets. 430-A1 R.T.E. 24AA Radio Transmitter. 503-A1 Pre-war FM Equipment. About 1000 sockets in special Government gear 5/1/45.	G. E. Westinghouse Nat'l Union R. C. A. Taylor Raytheon	807* 807* 1625* 807* T-21 RK-40
350-B	S	Beam power tube similar to 6L6. Designed for use in 124 Amplifier. 2 used with each set. 443-A (250 W) R.T.E. (5 in each). 503-A1 Pre-war FM Equipment. (Converted to use Elmac 4-125 during 1946). Proposed using in new side band equipment 5/1/46. About 10,000 sockets in special Government gear 5/1/45.	National Elmac	6L6* 4-125

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 54 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code</u> <u>Number</u>	<u>Price</u> <u>Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
351-A	S	A full-wave high vacuum rectifier similar in design to 345A tube for use in amplifiers and public address equipment. (443-A1 (1 kw) R.T.E. 430-A1 (100 Watt) R.T.E.) 451A (250 w) R.T.E. Can be replaced by 6X5 if not over 70 mls load. Used by E.R.P.	R. C. A.	6X5
352-A	S	A duo diode triode for use in 1,000 cycle ringer circuit SD-64419-01. Similar to 292A tube. (Merchandise control.)		
353-A	S	A three element cold cathode gas filled tube for use in 745 P.B.X. for generating audible ringing tone. Similar to 313C except for base. (Merchandise control)		
353-B	S	Same as 353A except that the main breakdown voltage limit is 165 to 225 volts DC. For use in AC operated message register circuit with #5 cross-bar system starting in April 1947. (Merchandise control.)		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 55 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

Code Number	Price Category	Description & Material in Which Used	Competition	Code
354-A	M	A mercury vapor filamentary type thyratron for use in J-862070 regulated rectifier for battery charging equipment in telephone plant. Estimated requirement for 6000 in 1947. Replaces 334A for new designs only. About 42 sockets in special Government gear 5/1/45. Heinz & Kaufmann use the codes 354-A, B, C, D, E, and F for transmitting triodes which are not comparable to our 354A. (Merchandise control.)		
355-A	M	A mercury vapor and argon filled filamentary thyratron for use in J-86207E and J rectifiers for battery charging equipment in telephone plant. Estimated demand for 7500 in 1947. About 34 sockets in special Government gear 5/1/45. (Merchandise control.)		
356-A	M.D.	A three element transmitting tube for high frequency use. Up to 100 mc at full power and 250 mc at reduced power. For use in 430A and B1 - 100 watt high frequency radio transmitter. Somewhat similar to the 304B tube. 1, 3, 10 & 50 KW Pre-war FM transmitters. Replaced by 356B. Station WHIO converted their 1 KW FM equipment to use Elmec 4-125.	R. C. A. Elmac	808* 4-125*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 56 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

Code Number	Price Category	Description & Material in Which Used	Competition	Code
356-B	M	Replaces 356A. Zirconium plate and different grid treatment - 10 watt higher rating. New line of AM Transmitters. Frequency doublers (4 sockets) on the Norfolk, Cape Charles job.	R.C.A. Elmac	808* 4-125*
357-A	M	A high frequency 350 watt air-cooled triode. Can be substituted for 241-B with an adapter or possibly a socket replacement. 430-B1 (100 Watt) R.T.E. and 443-A1 (1 kw) R.T.E. Equipment. 1, 3, 10 & 50 KW Pre-war FM Transmitter.	G. E. R. C. A.	GL-833-A* 833*
357-B	M	A high frequency 350 watt air cooled triode same as 357-A except that it has a Zirconium plate. Must be used in FM sockets and may be used in AM sockets after stocks of 357A's are exhausted.	G. E. R. C. A.	GL-833-A* 833*
358-A	S	A two element cold cathode discharge tube. This tube designed for associate use in equipment to give visual signal to the subscriber to replace the audible signal of the ringer. (Merchandise control.)		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 57 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
359-A	S	Cold cathode three element, filled with a mixture of rare gases principally neon. Telephone type for use in small secretarial system - known as 103A Key Equipment. (Merchandise control.)		
360-A	M.D.	Tube for Ortho-tronic hearing aid. Discontinued. Use Raytheon tube. (See D-164696)	Raytheon	
361-A	M.D.	Small tube for use in Ortho-tronic type audiphone. Intended primarily for resistance coupled voltage amplification or other uses within the limitations imposed by its very low current filament. It has a low microphonic level for a tube of comparable rating. Out of the hearing aid - 1942. Substitute Raytheon.	Raytheon	
362-A	M.D.	Small tube for use in Ortho-tronic type audiphone. Out of the hearing aid 1942.	Raytheon	507AX
363-A	L	Filamentary pentode designed for use in Radio Communication Project for Virginia Capes. 350 watts.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 58 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
364-A	M	Filamentary triode primarily required for use in Radio Communication Project for Virginia Capes.		
365-A	M.D.	Full wave rectifier. Developed for Virginia Capes Project. Only five made in B.T.L. Discontinued - never incorporated in any equipment.		
366-A	M.D.	Pentode developed for Virginia Capes Project but never used therein.		
367-A	M	Beam power amplifier. Developed for use in Virginia Capes Project. Local Video amplifiers can be replaced by 350-B in some cases. (Merchandise control.)	National Union Field	616* 807*
368-A	M	Filamentary air cooled triode intended for high frequency oscillator and amplifier applications of approximately 1.5 to 3 watts peak output. Similar to D-159764.		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 59 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code</u> <u>Number</u>	<u>Price</u> <u>Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
368-AS	M.D.	Same as 368A except that it is a "single ender". Similar to 703A.	Tungsol	368AS
369-A		Water cooled triode approximately 25 kw. Developed for use in Composite Stations. Never manufactured.	Federal	
370-A	M.D.	Triode with filamentary type cathode. Class C operation - 3 & 50 KW Pre-war FM aircooled. Dis- continued because new FM allocations required a different tube.		
371-B	M.D.	Rectifier tube developed for use as component of Rectifier being used in Pre-war Government Project. More rigid than 371A which it replaced.	Nat'l Union Electronic- Enterprises United Elec- tronics G. E.	271* GL-8020*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 60 of 86 Pages

Ball & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
372-A	S	Three element cold cathode gas filled tube. May be used as a relay, voltage regulator or rectifier. Intended primarily for use in the H5 telephone set mounting, as used in 306 type telephone sets. Tube is same as 333A except length of flexible leads are shorter and screw omitted from base. (Merchandise control.)		
373-A	S	Pentode voltage amplifier designed for K2 Carrier System. (Merchandise control.)		
374-A	S	Pentode power amplifier designed for K2 Carrier System. Partially superseded by 398A tube. (Merchandise control.)		
375-A	S	Cathode type beam tetrode. For use at audio frequencies. Primarily intended for general use in Central Office battery supply. Limited to 48 volts. (Merchandise control.)		
376-A	M.D.	Three element cold cathode tube. (Merchandise control.)		

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

Western Electric Company
Radio Division
Department 9715

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

September 10, 1946
Page 61 of 86 Pages

CHARACTERISTIC DATE

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
376-B	S	Three element cold cathode tube. Replaces 376-A and has a higher current rating. Initially used in the 1-C-1 Common Carrier Terminal Equipment. Radio power line carrier, a companion tube of the 398-A, 399-A, 400-A, and 401-A tubes. Might possibly be used in the AC Key Pulsing Senders and Receivers for the #4 and #5 cross-bar equipment. Estimated demand 1947 - 25,000. (Merchandise control.)	R. C. A.	Specially heated OA4G
378-A	M.D.	Never manufactured, but 705A is identical.		
379-A	L	An improved 279A Vacuum tube with grid connection in different location. A.T. & T. unable to use account grid connection and will continue to use 279A. 71A and B, 90A and 6071A Amplifiers (1000 watts) 304A Radio Transmitting Equipment. D-96847 Amplifiers.	Heinz & Kaufmann	2054-A
380-A	S	Cathode type diode - high frequency applications, type "L" Coaxial Systems and 1A Altimeter (Receiver and test set). Replaces D-157653. No base.		
(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value. (*) With modifications.				

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

September 10, 1946
Page 62 of 86 Pages

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
381-A	S	Same as 380-A except that interelectrode capacitance plate to heater and cathode is 1.4 mmf (rather than 1.1) and has octal base.		
382-A	S	Triode with an indirectly heated cathode intended for miscellaneous low power applications through audio and high frequencies. No base. Originally developed for use in coaxial cable. Used in condenser transmitter amplifier. RA-1095. Replaces D-157591.		
383-A	S	Same as 382-A except has octal base. Originally designed for use in short wave multiplex type K carrier, UHF 12 channel job.		
384-A	M	Pentode with an indirectly heated cathode. Audio and high frequency applications. Unbased. Used on L carrier amplifier, large requirements. (Consider using the 6AK5 instead.)	Heinz & Kaufmann	HQ-201*
385-A	S	Same as 384A except has octal base. Slight difference in plate resistance. 156 sockets in the model RBQ receiver and 302 sockets in the 42A1 carrier repeater. (12/20/44). Consider 6AK5 for any new applications.	Heinz & Kaufmann	HQ-201*

{S} Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
{*} With modifications.

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 63 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
386-A	M	Pentode with indirectly heated cathode. Unbased - low power applications - audio and high frequencies. Used on L carrier amplifiers. New York to Philadelphia coaxial. Large requirements. (Merchandise control.)		
387	M	Same as 386-A except has octal base and top cap - slight differences in amplification factor, plate resistance and transconductance. Replaces D-159512.		
388-A	M.D.	Filamentary air cooled triode. Unbased. High frequency oscillator and amplifier. AN/APQ-2 Equipments made by Delco. Transmitter of 1A Altimeter - formerly D-156548.		
389-AA	L	Filamentary forced-air cooled triode. 10 KW Pre-war FM Transmitter. Will use at Station WHAS after change to new frequencies.	G. E.	889-R*

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

CHARACTERISTIC DATE

Western Electric Company
Radio Division
Department 9715

September 10, 1946
Page 64 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

Code Number	Price Category	Description & Material in Which Used	Competition	Code
393-A	S	Filamentary thyatron containing both argon and mercury vapor. About 14,000 sockets in special Government gear 5/1/45. Will probably replace the 323-A tube in D, J, G, H, K, and 2067-F rectifiers used in KS-15123 rectifier (Railroad job.)	Continental G. E.	CE-393-A 393-A 3-C-23*
394-A	S	Filamentary thyatron, argon and mercury vapor filled. Power supply tube for the J-86207-G and H rectifiers for carrier telegraph and the J-86207-N rectifier inverter. About 3970 sockets in special Government gear 5/1/45. Also used in X-61680-B regulated tube (package C carrier) rectifier (2 each) in telephone work. Probable post-war use in regulation of industrial power supplies. Both Mackay and RCA Communications bought surplus Government Radio TWX equipments which use 394-A tubes. Trucksess is assigning a J number so that X-61680-B rectifiers will be recognized as regular telephone plant when the purchase of Government Package C Carriers is completed. C.E. Budd estimates 10,000 operating sockets in spiral four 5/1/46.	Kuthe' Chatham Electric	

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.

Western Electric Company
Radio Division
Department 9715

October 14, 1946
Page 65 of 86 Pages

Bell & Commercial Electron Tubes
Confidential - For Distribution Only Within the Company

CHARACTERISTIC DATE

<u>Code Number</u>	<u>Price Category</u>	<u>Description & Material in Which Used</u>	<u>Competition</u>	<u>Code</u>
395-A	S	Three element, double gap, cold cathode gas filled tube for use as a relay, rectifier or voltage regulator. Designed to take mechanical shock. Unbased. Mine detection devices and other Government applications. About 92,000 sockets in special Government gear 5/1/45, practically none of which will ever require replacement. X TFDC devices (A.B. Kowenhoven). Has advantages over 727-A tube.		
396-A	S	Same as 2C51. Bell System code number assigned at A. T. & T. request.		
397-A	M	Same as 2K56 velocity modulated local oscillator and transmitting tube designed for the 4000 MC Radio Relay System (Boston - New York Link).		
398-A	S	Filamentary power pentode similar to the 374-A. One socket in each J-98701 A Carrier Tel. Terminal (Subset) and J-98701B (Terminal Equipment). Companion tubes are 376B, 399A, 400A and 401A.		
399-A	S	Filamentary miniature pentode similar to RMA code IT4. One socket in each J-98701A Carrier Tel. Terminal (Subset) and two sockets in each J-98701B (Terminal Equipment). Companion tubes are 376B, 398A, 400A and 401A.	Field	IT4

(S) Small value. (M) Medium value. (M.D.) Manufacture discontinued. (L) Large value.
(*) With modifications.